

3,7W / 335lm / 4000K / Medium 26° /  
50x50mm


64805




Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10  
3-step MacAdam / Power supply not included  
IP44 | 100mA




	4000K	Light Source		Luminaire	
	Power	3,7W		3,7W	
	Flux	415lm		335lm	
	Efficiency	112lm/W		91lm/W	
	LOR	-		81%	
	UGR	-		<13	



Beam angle  
Medium 26°

Application



Weight  
0.08Kg



- Mandatory

**59088 Driver On/Off [100mA]**

138x30x21mm

59089 Driver DALI [100mA]

144x30x21mm

### 59090 Driver PhaseCut [100mA]

122x41x23mm

**59091 Driver 1-10V [120mA]**

130x30x20mm

Optional

**59148 Louvre**

ø25x4mm

**59149 Elliptical diffuser**

ø25x4mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

The 5-year guarantee applies only when the luminaire and driver are supplied together.

### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class F  
Model Identifier BXRH-40G1000-B-83