



3,7W / 285lm / 2700K / On/Off / Medium
26° / ø50mm

64820


Design: O/M


Ceiling-recessed luminaire made of aluminium die-cast.

Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply not included
IP65 | 100mA



 LED	2700K	Light Source	Luminaire
Power	3,7W		3,7W
Flux	375lm		285lm
Efficiency	101lm/W		77lm/W
LOR	-		76%
UGR	-		<10



Beam angle
Medium 26°


Application



Weight
0.08Kg



045



Finishes

- .04 Matt White
● .05 Matt Black

Mandatory

59088 Driver On/Off [100mA]

138x30x21mm

59089 Driver DALI [100mA]

144x30x21mm

59090 Driver PhaseCut [100mA]

122x41x23mm

59091 Driver 1-10V [120mA]



130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

The 5-year guarantee applies only when the luminaire and driver are supplied together.


Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F
Model Identifier BXRH-27G1000-B-83





Go
IP65

Driver DALI [1 luminaire] 59088



Driver On/Off for Go ø50 [100mA]
230Vac | 50/60Hz | Class II


Weight	Finishes
0,1Kg	.99



Go IP65

Driver DALI [1 luminaire]

59089



Driver DALI for Go ø50 [100mA]
230Vac | 50/60Hz | Class II

Weight
0,06Kg


Finishes
.99



Go IP65

Driver PhaseCut [1 luminaire]



59090



Driver PhaseCut for Go ø50
[100mA]
230Vac | 50/60Hz | Class II

Weight
0,08Kg

Finishes
.99






Go IP65

Driver 1-10V [1 luminaire]

59091



Driver 1-10V for Go ø50 [120mA]
230Vac | 50/60Hz | Class II

Weight
0,07Kg

Finishes
.99

