




Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10  
3-step MacAdam / Power supply not included  
IP65 | 100mA



|  |                     |                  |
|--|---------------------|------------------|
|  <b>3500K</b> | <b>Light Source</b> | <b>Luminaire</b> |
| <b>Power</b>   | <b>3,7W</b>         | <b>3,7W</b>      |
| <b>Flux</b>  | <b>410lm</b>        | <b>310lm</b>     |
| <b>Efficiency</b>  | <b>111lm/W</b>      | <b>84lm/W</b>    |
| <b>LOR</b>   | -                   | <b>76%</b>       |
| <b>UGR</b>   | -                   | <b>&lt;16</b>    |



Beam angle  
Flood 42°

Application



Weight  
0.08Kg



Finishes

- .04 Matt White
- .05 Matt Black

Mandatory

**59088** Driver On/Off [100mA]

138x30x21mm

**59089** Driver DALI [100mA]

144x30x21mm

**59090** Driver PhaseCut [100mA]

122x41x23mm

**59091** Driver 1-10V [120mA]

130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

The 5-year guarantee applies only when the luminaire and driver are supplied together.

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier BXRH-35G1000-B-83