



3,7W / 310lm / 3500K / Flood 60° / ø50mm

64828

Design: O/M

Ceiling-recessed luminaire made of aluminium die-cast.


Recessing system with spring clips.


LED CRI>90 / >50.000h, L80/B10

3-step MacAdam / Power supply not included

IP65 | 100mA



 LED	3500K	Light Source	Luminaire
Power	3,7W		3,7W
Flux	410lm		310lm
Efficiency	111lm/W		84lm/W
LOR	-		76%
UGR	-		<22



Beam angle
Flood 60°


Application



Weight
0.08Kg



045



Finishes

- .04 Matt White
● .05 Matt Black

Mandatory

59088 Driver On/Off [100mA]

138x30x21mm

59089 Driver DALI [100mA]

144x30x21mm

59090 Driver PhaseCut [100mA]

122x41x23mm

59091 Driver 1-10V [120mA]

130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

The 5-year guarantee applies only when the luminaire and driver are supplied together.

Data according to regulations

2019/2020/EU supplemented by 2021/341 [2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier BXRH-35G1000-B-83