





Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10  
3-step MacAdam / Power supply not included  
IP65 | 100mA




 <b>4000K</b>	<b>Light Source</b>		<b>Luminaire</b>	
<b>Power</b>	<b>3,7W</b>		<b>3,7W</b>	
<b>Flux</b>	<b>415lm</b>		<b>315lm</b>	
<b>Efficiency</b>	<b>112lm/W</b>		<b>85lm/W</b>	
<b>LOR</b>	<b>-</b>		<b>76%</b>	
<b>UGR</b>	<b>-</b>		<b>&lt;10</b>	



**Beam angle**  
**Medium 26°**

**Application**



**Weight**  
**0.08Kg**



Ø45



#### Finishes

- .04 Matt White
- .05 Matt Black

#### Mandatory

**59088** Driver On/Off [100mA]

138x30x21mm

**59089** Driver DALI [100mA]

144x30x21mm

**59090** Driver PhaseCut [100mA]

122x41x23mm

**59091** Driver 1-10V [120mA]

130x30x20mm

#### Optional

**59150** Frosted Glass

ø28x2mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

The 5-year guarantee applies only when the luminaire and driver are supplied together.

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 [2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier BXRH-40G1000-B-83