




Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10  
3-step MacAdam / Power supply not included  
IP65 | 300mA / 150mA




 LED	2700K	Light Source	Luminaire
Power	10W / 5W		10W / 5W
Flux	1505lm / 755lm		1130lm / 565lm
Efficiency	151lm/W		113lm/W
LOR	-		75%
UGR	-		<10



Beam angle  
Spot 20°

Application



Weight  
0.37Kg



Ø90



#### Finishes

- .04 Matt White
- .05 Matt Black

#### Mandatory

**59109** Driver On/Off [300mA]

147x43x30mm

**59108** Driver On/Off [150mA]

147x43x30mm

**59111** Driver DALI [300mA]

144x30x21mm

**59110** Driver DALI [150mA]

144x30x21mm

**59113** Driver PhaseCut [300mA]

102x51x30mm

**59112** Driver PhaseCut [150mA]

102x49x29mm

**59115** Driver 1-10V [300mA]

130x30x20mm

**59114** Driver 1-10V [150mA]

130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

The 5-year guarantee applies only when the luminaire and driver are supplied together.

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 [2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E  
Model Identifier BXRE-27G10FB-C-83