





Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply not included
IP65 | 400mA / 200mA



 LED	2700K		
		Light Source	Luminaire
Power		14W / 7W	14W / 7W
Flux		2270lm / 1135lm	1725lm / 865lm
Efficiency		162lm/W	123lm/W
LOR		-	76%
UGR		-	<19



Beam angle
Flood 60°



Weight
0.37Kg



Ø90



Finishes

- .04 Matt White
- .05 Matt Black

Mandatory

59117 Driver On/Off [400mA]

147x43x30mm

59116 Driver On/Off [200mA]

147x43x30mm

59119 Driver DALI [400mA]

144x30x21mm

59118 Driver DALI [200mA]

144x30x21mm

59121 Driver PhaseCut [400mA]

111x22x52mm

59120 Driver PhaseCut [180mA]

102x49x29mm

59123 Driver 1-10V [400mA]

163x30x21mm

59122 Driver 1-10V [200mA]

130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

The 5-year guarantee applies only when the luminaire and driver are supplied together.

Data according to regulations

2019/2020/EU supplemented by 2021/341 [2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains a light source of efficiency class E

Model Identifier BXRE-27G20FB-C-83