

3,7W / 285lm / 2700K / Flood 42° /
50x50mm

64861



Design: O/M

Ceiling-recessed luminaire made of aluminium die-cast.

Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply not included
IP65 | 100mA


LED	2700K	Light Source	Luminaire
Power		3,7W	3,7W
Flux		375lm	285lm
Efficiency		101lm/W	77lm/W
LOR		-	76%
UGR		-	<16

Beam angle
Flood 42°

Application

Weight
0.08Kg

45x45



Finishes

- .04 Matt White
- .05 Matt Black

Mandatory

59088 Driver On/Off [100mA]

138x30x21mm

59089 Driver DALI [100mA]

144x30x21mm

59090 Driver PhaseCut [100mA]

122x41x23mm

59091 Driver 1-10V [100mA]

130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class F
Model Identifier BXRH-27G1000-B-83