



Go
IP65 Square

6,7W / 3,4W / 800lm / 400lm / 3500K /
Medium 34° / 75x75mm


64879



Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply not included
IP65 | 200mA / 100mA



| | | | |
|---|----------------|--------------|---------------|
|  LED | 3500K | Light Source | Luminaire |
| Power | 6,7W / 3,4W | | 6,7W / 3,4W |
| Flux | 1055lm / 530lm | | 800lm / 400lm |
| Efficiency | 157lm/W | | 119lm/W |
| LOR | - | | 76% |
| UGR | - | | <16 |



Beam angle
Medium 34°

Application



Weight
0.21Kg



65x65



Finishes

- .04 Matt White
- .05 Matt Black

Mandatory

59101 Driver On/Off [200mA]

147x43x30mm

59100 Driver On/Off [100mA]

110x40x21mm

59103 Driver DALI [200mA]

144x30x21mm

59102 Driver DALI [100mA]

144x30x21mm

59105 Driver PhaseCut [180mA]

102x49x29mm

59104 Driver PhaseCut [100mA]

122x41x23mm

59107 Driver 1-10V [200mA]

130x30x20mm

59106 Driver 1-10V [120mA]

130x30x20mm

Optional

59142 Flush accessory (12.5mm ceilings)

140x80x14mm

59143 Flush accessory (15mm ceilings)

140x80x17mm

59153 Frosted Glass

ø40x2mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

The 5-year guarantee applies only when the luminaire and driver are supplied together.

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E
Model Identifier BXRE-35G10FB-C-83