

5,6W / 350lm / 3000K / On/Off / Medium  
40° / ø45mm


64888




Design: O/M + Bartenbach GmbH  
Surface spotlight with die-cast aluminium body with electrostatic 100% polyester paint finish.  
Orientable by 150° horizontal rotation and 330° vertical rotation.  
Driver to be ordered separately.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Driver to be ordered separately.  
IP20 / 450mA



 3000K	Light Source	Luminaire
Power	5,6W	5,6W
Flux	460lm	350lm
Efficiency	82lm/W	50lm/W
LOR	-	76%
Operating Condition	-	Current source



Beam angle  
Medium 40°

Application

Weight  
0,30Kg



#### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

#### Mandatory

**59084** Driver On/Off [Up to 2 luminaires]

140x30x21mm

**59085** Driver On/Off [Up to 3 luminaires]

163x30x21mm

**59086** Driver DALI [Up to 2 luminaires]

140x30x21mm

**59087** Driver DALI [Up to 3 luminaires]

163x30x21mm

#### Optional

**59072** 1/4 CTO

$\varnothing 35 \times 1,1\text{mm}$

**59073** 1/2 CTO

$\varnothing 35 \times 1,1\text{mm}$

**59074** Louvre

$\varnothing 35 \times 2\text{mm}$

**59075** Soft diffuser

$\varnothing 35 \times 2\text{mm}$

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class G  
Model Identifier 4053560290L