

## Tubo Pro Surface

67W / 6390lm / 4000K / DALI / Wide flood  
76° / 2408mm

64914



Design: Eduardo Souto de Moura  
Surface luminaire with tubular semi frosted PMMA body with 70mm diameter.  
Clear polycarbonate end caps with marked installation angles.  
Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.  
Equipped with 2m cable (5x0.75 mm²).  
Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam  
Power supply included.  
IP44 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		67W	78,1W
Flux		9400lm	6390lm
Efficiency		142lm/W	82lm/W
LOR		-	68%
UGR		-	<19



Beam angle  
Wide flood 76°

Application



Weight



Finishes

○ .01 White / RAL 9010

Mandatory

59163 Surface fitting accessor (>1600mm)

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class E  
Model Identifier 4053560084