

## Tubo Pro Pendant

27W / 2550lm / 4000K / DALI / Wide flood  
76° / 1544mm

64935



Design: Eduardo Souto de Moura  
Pendant luminaire with tubular semi frosted PMMA body with 70mm diameter.  
Clear polycarbonate end caps with marked installation angles.  
Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.  
Equipped with 2m cable (5x0.75 mm²).  
Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam  
Power supply included.  
IP44 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		27W	32,3W
Flux		3750lm	2550lm
Efficiency		142lm/W	79lm/W
LOR		-	68%
UGR		-	<16



Beam angle  
Wide flood 76°

Application

Weight



### Finishes

○ .01 White / RAL 9010

### Mandatory

59146 Pendant fitting accessory

Data according to regulations  
2019/2020/EU supplemented by 2021/341 [2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class D  
Model Identifier 4053560084