





Design: O/M + Bartenbach GmbH
Ceiling-recessed luminaire with aluminium die-cast body with electrostatic 100% polyester paint finish. Focal lens with complex surfaces to provide a focal point through an 8mm aperture for low glare illumination.
Driver to be ordered separately.

LED CRI>90 / >50.000h, L80/B10
2-step MacAdam
IP65



 3000K	Light Source	Luminaire
Power	2,1W	2,1W
Flux	200lm	90lm
Efficiency	95lm/W	33lm/W
LOR	-	45%
UGR	-	<10



Beam angle
Spot 15°

Application

Weight
0,09Kg

mm

Ø33



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

- 59000** Trimless accessory
 $\varnothing 32 \times 35$ mm
- 59036** Trim accessory
 $\varnothing 38 \times 75$ mm
- 59157** Driver On/Off [1 to 5 luminaires]
 $158 \times 22 \times 19$ mm
- 59158** Driver DALI [1 to 6 luminaires]
 $113 \times 24 \times 20$ mm

Optional

- 59083** Removal tool
- 59001** 1/4 CTO
 $\varnothing 17 \times 1,1$ mm
- 59002** 1/2 CTO
 $\varnothing 17 \times 1,1$ mm
- 59003** Louvre
 $\varnothing 17 \times 3$ mm
- 59004** Soft diffuser
 $\varnothing 17 \times 1$ mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Drivers On-Off for more than one luminaire and Drivers DALI must be placed remote