





Design: O/M + Bartenbach GmbH  
Ceiling-recessed luminaire with aluminium die-cast body with electrostatic 100% polyester paint finish. Focal lens with complex surfaces to provide a focal point through an 8mm aperture for low glare illumination.  
Driver to be ordered separately.


LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam  
IP65



 4000K	Light Source	Luminaire
Power	2,1W	2,1W
Flux	220lm	100lm
Efficiency	105lm/W	37lm/W
LOR	-	45%
UGR	-	<10



Beam angle  
Spot 15°

Application  


Weight  
0,09Kg

mm

Ø33



#### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

#### Mandatory

- 59000** Trimless accessory  
 $\varnothing 32 \times 35$ mm
- 59036** Trim accessory  
 $\varnothing 38 \times 75$ mm
- 59157** Driver On/Off [1 to 5 luminaires]  
 $158 \times 22 \times 19$ mm
- 59158** Driver DALI [1 to 6 luminaires]  
 $113 \times 24 \times 20$ mm

#### Optional

- 59083** Removal tool
- 59001** 1/4 CTO  
 $\varnothing 17 \times 1,1$ mm
- 59002** 1/2 CTO  
 $\varnothing 17 \times 1,1$ mm
- 59003** Louvre  
 $\varnothing 17 \times 3$ mm
- 59004** Soft diffuser  
 $\varnothing 17 \times 1$ mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

Drivers On-Off for more than one luminaire and Drivers DALI must be placed remote