


Design: O/M + Bartenbach GmbH  
Ceiling-recessed luminaire with aluminium die-cast body with electrostatic 100% polyester paint finish. Focal-lens with complex surfaces to provide a focal point through an 8mm aperture for low glare illumination.  
Supplied with fermacell® plasterboard fiber recessing accessory or plasterboard.  
Driver to be ordered separately.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam  
IP65



LED	4000K	Light Source	Luminaire
Power		2,1W	2,1W
Flux		220lm	110lm
Efficiency		105lm/W	41lm/W
LOR		-	50%
UGR		-	<19




Beam angle  
Spot 16°



Weight  
0,96Kg



201x201



#### Finishes

● .02 Black / RAL 9005

#### Mandatory

**59157** Driver On/Off [1 to 5 luminaires]

158x22x19mm

**59158** Driver DALI [1 to 6 luminaires]

113x24x20mm

#### Optional

**59013** Ceiling access hatch for drivers

365x365x13mm

**59034** Plasterboard metal profile for Nub

250x47x18mm

Optional (positioned at the factory)

**59001** 1/4 CTO

ø17x1mm

**59002** 1/2 CTO

ø17x1mm

**59003** Louvre

ø17x3mm

**59004** Soft diffuser

ø17x1mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)