



Design: O/M + Bartenbach GmbH
Ceiling-recessed luminaire with aluminium die-cast body with electrostatic 100% polyester paint finish. Focal-lens with complex surfaces to provide a focal point through an 8mm aperture for low glare illumination.
Supplied with fermacell® plasterboard fiber recessing accessory or plasterboard.
Driver to be ordered separately.

LED CRI>90 / >50.000h, L80/B10
2-step MacAdam
IP65



 4000K	Light Source	Luminaire
Power	2,1W	2,1W
Flux	220lm	110lm
Efficiency	105lm/W	41lm/W
LOR	-	50%
UGR	-	<19




Beam angle
Spot 16°



Weight
0,96Kg



201x201



Finishes

● .02 Black / RAL 9005

Mandatory

59157 Driver On/Off [1 to 5 luminaires]

158x22x19mm

59158 Driver DALI [1 to 6 luminaires]

113x24x20mm

Optional

59013 Ceiling access hatch for drivers

365x365x13mm

59034 Plasterboard metal profile for Nub

250x47x18mm

Optional (positioned at the factory)

59001 1/4 CTO

ø17x1mm

59002 1/2 CTO

ø17x1mm

59003 Louvre

ø17x3mm

59004 Soft diffuser

ø17x1mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com