

26W / 1955lm / 3000K / DALI / Wallwasher /  
 1200mm

**65448**

**Structure**

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

**Modules**

- A inVision Module

Design: O/M + Bartenbach GmbH

inVision module with housing and perforated cover plate made of aluminium with textured-paint finish.

 LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam  
 Power supply included.  
 IP20 | 230Vac | 50/60Hz


| LED               | 3000K | Light Source | Luminaire |
|-------------------|-------|--------------|-----------|
| <b>Power</b>      |       | 26W          | 30,7W     |
| <b>Flux</b>       |       | 2570lm       | 1955lm    |
| <b>Efficiency</b> |       | 102lm/W      | 64lm/W    |
| <b>LOR</b>        |       | -            | 76%       |
| <b>UGR</b>        |       | -            | -         |


**Beam angle**  
**Wallwasher**
**Application**

**Weight**  
**0,6Kg**

**Finishes**

- .01 White / RAL 9010
- .02 Black / RAL 9005

 For the specific supply of "DALI 2" drivers, please contact:  
[support@om-light.com](mailto:support@om-light.com)

 Choose the length and layout of the system exactly as you want it, to  
 model the right lighting functions for different tasks. For further  
 information please contact: [support@om-light.com](mailto:support@om-light.com)