

6,5W / 490lm / 3000K / DALI / Flood 52° /
150mm

60077



Design: O/M + Bartenbach GmbH

Luminaire with housing of aluminium profile with electrostatic 100% polyester paint with textured-finish.

Focal-lens with complex surface and individual complex surface rips to provide a focal point through an aperture for glare free area illumination.

Special springs available on request.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz

LED 3000K

Light Source

Luminaire

Power

6,5W

8,1W

Flux

645lm

490lm

Efficiency

99lm/W

94lm/W

LOR


-

76%

UGR

-

<16

Beam angle
Flood 52°

Application

Weight
0,22Kg

mm

26x144

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains a light source of efficiency class E
Model Identifier 4053560263H