

One

9,8W / 550lm / 2700K / On/Off / Spot 15° / ø85mm

60131



Design: O/M + Bartenbach GmbH


Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam. Fitting accessories for different applications are available.

LED CRI>90 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz



● 2700K	Light Source	Luminaire
Power	9,8W	12,3W
Flux	955lm	550lm
Efficiency	97lm/W	45lm/W
LOR	-	58%
UGR	-	<10



Spot 15°


Application

1

Weight **0,58Kg**



@078 (trim version)



Finishes

.01 White / RAL 9010.02 Black / RAL 9005

Optional

59014 Accessory 12,5mm ceilings (flush installation)

150×91×20mm

59038 Accessory 10-40mm ceilings (acoustic ceiling) 156x100x78mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class F
Model Identifier 2053560245H