

9,8W / 770lm / 3000K / On/Off / Medium
40° / Ø85mm

60149




Design: O/M + Bartenbach GmbH
 Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.
 Lightcore optics for defined and perfectly controlled beam of light.
 Easy recessing system with spring clips.
 Fitting accessories for different applications are available.

LED CRI>90 / >50.000h, L80/B10
 2-step MacAdam / Power supply included.
 IP20 | 230Vac | 50/60Hz



	3000K	Light Source	Luminaire
Power	9,8W	12,3W	
Flux	1035lm	770lm	
Efficiency	106lm/W	63lm/W	
LOR	-	74%	
UGR	-	<10	



Beam angle
Medium 40°



Weight
0,53Kg

mm

Ø78 (trim version)

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Optional


59014 Accessory 12,5mm ceilings (flush installation)

150x91x20mm

59038 Accessory 10-40mm ceilings (acoustic ceiling)

156x100x78mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com



Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains a light source of efficiency class F

Model Identifier 2053560257H