

## One IP65

9,8W / 530lm / 3000K / DALI / Spot 15° / ø85mm

60207




Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam. Fitting accessories for different applications are available.

LED CRI>90 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP65 | 230Vac | 50/60Hz



3000K	Light Source	Luminaire
Power	9,8W	12,3W
Flux	1035im	530lm
Efficiency	106lm/W	43lm/W
LOR	-	51%
UGR	-	<10




Beam angle Spot 15°

Application



Weight 0,58Kg

mm	Ø78 (trim version)



## Finishes

O .01 White / RAL 9010

.02 Black / RAL 9005

## Optional

**59014** Accessory 12,5mm ceilings (flush installation) 150x91x20mm

**59038** Accessory 10-40mm ceilings (acoustic ceiling) 156x100x78mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier 2053560257H