



9,8W / 850lm / 3000K / DALI / Flood 56° / ø85mm

60211



Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Lightcore optics for defined and perfectly controlled beam of light.

Easy recessing system with spring clips.


Fitting accessories for different applications are available.

LED CRI>90 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP65 | 230Vac | 50/60Hz



(ϵ
---	------------

● 3000K	Light Source	Luminaire
Power	9,8W	12,3W
Flux	1035lm	850lm
Efficiency	106lm/W	69lm/W
LOR	-	82%
UGR	-	<16



Beam angle Flood 56°


Application



Weight 0,53Kg



@078 (trim version)



Finishes

O .01 White / RAL 9010 ● .02 Black / RAL 9005

Optional

59014 Accessory 12,5mm ceilings (flush installation)

150x91x20mm

59038 Accessory 10-40mm ceilings (acoustic ceiling) 156×100×78mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier 2053560257H