



9,8W / 880lm / 4000K / On/Off / Medium 40° / ø85mm

60217

Design: O/M + Bartenbach GmbH

Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Lightcore optics for defined and perfectly controlled beam of light.

Easy recessing system with spring clips.


Fitting accessories for different applications are available.

LED CRI>80 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP65 | 230Vac | 50/60Hz





1000K	Light Source	Luminaire
Power	9,8W	12,3W
Flux	1360lm	880lm
Efficiency	139lm/W	72lm/W
LOR	-	65%
UGR	-	<10




Beam angle Medium 40°

Application



Weight 0,53Kg

mm @078 (trim version)



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

Optional

59014 Accessory 12,5mm ceilings (flush installation)

150x91x20mm

59038 Accessory 10-40mm ceilings (acoustic ceiling) 156×100×78mm

The cutout dimensions are for plasterboard ceilings. For other type of $% \left\{ 1,2,\ldots ,n\right\}$ material please contact: support@om-light.com

Data according to regulations 2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier 2053560247H