

One **IP65**

4,5W / 510lm / 4000K / DALI / Flood 56° / ø85mm

60226



Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Lightcore optics for defined and perfectly controlled beam of light.

Easy recessing system with spring clips.

Fitting accessories for different applications are available.


LED CRI>80 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP65 | 230Vac | 50/60Hz





| 4000K | Light Source | Luminaire |
|--------------|--------------|-----------|
| Power | 4,5W | 5,8W |
| Flux | 620lm | 510lm |
| Efficiency | 138lm/W | 88Im/W |
| LOR | - | 82% |
| UGR | - | <16 |

@078 (trim version)




Beam angle Flood 56°

Application



Weight 0,53Kg

| _ | | | |
|----|--|--|--|
| mm | | | |



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

Optional

59014 Accessory 12,5mm ceilings (flush installation)

150x91x20mm

59038 Accessory 10-40mm ceilings (acoustic ceiling) 156×100×78mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E Model Identifier 2053560247L