

One Plus

4,5W / 380lm / 3000K / DALI / Medium 40° / ø95mm

60236



Design: O/M + Bartenbach GmbH

Ceiling-recessed luminaire with die-cast aluminium body and heat sink.

Orientable by 30° on the horizontal axis and 355° on the vertical axis.

Reflector built based on micro surfaces with complex geometry coated with aluminium alloy, creating a high-gloss, entirely mirrored surface. Accurate reflector for a defined and controlled beam of light, achieving the maximum efficiency.

Reduced height <67mm.


Recessing accessory for trimless version supplied separately.

LED CRI>90 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz





3000 K	Light Source	Luminaire
Power	4,5W	5,8W
Flux	520lm	380lm
Efficiency	116lm/W	66lm/W
LOR	-	73%
UGR	-	<10



Beam angle Medium 40°


Application



Weight 0,42Kg



@090 (trim version)



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

■ .21 Black+White

59015 Accessory 12,5mm ceilings (flush installation) 150×101×20mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier 2053560257L