

Onit Track (230v)

10W / 910Im / 3000K / DALI / Spot 12° / ø45mm

60322



Design: O/M

Adjustable spotlight with aluminium body for installation on three-phase track.


The spotlight can be rotated up to 90° horizontally and 330° vertically.

Accessories available separately and easily applicable after installation.

LED CRI>90 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz



3000K	Light Source	Luminaire
Power	10W	12,5W
Flux	1035lm	910lm
Efficiency	104lm/W	73lm/W
LOR	-	0.88
UGR	-	<13




Beam angle Spot 12°

Application



Weight

nm.



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

Optional

59016 Elliptical refractor

Ø39x0.5mm 59017 Soft diffuser

Ø39x0,5mm

59018 Louvre

Ø39x3mm **59019** Snoot 72mm

Ø45×72

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier 2053560257H