

10W / 1090lm / 4000K / On/Off / Medium  
28° / ø100mm

60380



Design: O/M


Ceiling-recessed luminaire made of aluminium die-cast.

Recessing accessory for flush version supplied separately.

LED CRI>80 / >50.000h, L80/B10  
3-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power	10W	12,5W	
Flux	1450lm	1090lm	
Efficiency	145lm/W	87lm/W	
LOR	-	75%	
UGR	-	<19	




Beam angle  
Medium 28°



Weight  
0,5Kg



Ø95 (trim version)



### Finishes

- .04 Matt White
- .05 Matt Black

### Optional

- 59066** Flush accessory (12.5mm ceilings)  
201x17mm
- 59067** Flush accessory (15mm ceilings)  
201x19,5mm
- 59068** Flush accessory (25mm ceilings)  
201x29,5mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class E  
Model Identifier BXR-40E2000-C-73