

## **Beam IP54**

10W / 1105lm / 4000K / DALI / Flood 46° / ø100mm

60466




Ceiling-recessed luminaire made of aluminium die-

Recessing accessory for flush version supplied separately.

LED CRI>80 / >50.000h, L80/B10 3-step MacAdam / power supply included IP54 | 230Vac | 50/60Hz



1000K			
	Light Source	Luminaire	
Power	10W	12,5W	
Flux	1450lm	1105lm	
Efficiency	145lm/W	88lm/W	
LOR	-	76%	
UGR	-	<22	



Beam angle Flood 46°


Application



Weight 0,5Kg

mm

Ø95 (trim version)



## Finishes

O .04 Matt White

.05 Matt Black

Optional

59066 Flush accessory (12.5mm ceilings)

201×17mm

59067 Flush accessory (15mm ceilings)

201×19,5mm

59068 Flush accessory (25mm ceilings)

201×29,5mm

For the specific supply of "DALI 2" drivers, please contact:

support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E Model Identifier BXRC-40E2000-C-87