

17W / 1800lm / 4000K / DALI / Flood 64° /
1493mm

60497

Product timing available by request




Design: OM + Bartenbach GmbH
 Recessed luminaire with housing made of aluminium with 25 micron maximum corrosion resistance anodization in matte finish or electrostatic 100% polyester paint with textured finish.
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured finish.
 Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.
 Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
 Power supply included.
 IP20 | 230Vac | 50/60Hz



	4000K	Light Source	Luminaire
Power	17W	20,7W	
Flux	2250lm	1800lm	
Efficiency	132lm/W	87lm/W	
LOR	-	80%	
UGR	-	<13	



Beam angle
Flood 64°



Weight
2,4Kg

□ mm

47x1483

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

51027 Recessed fitting accessory

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com
 O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

