

## inFinit Recessed

53W / 6000lm / 4000K / DALI / Wide flood 76° / 2933mm

60505

## Product timing available by request

Design: OM + Bartenbach GmbH Recessed luminaire with housing made of aluminium

with 25 micron maximum corrosion resistance anodization in matte finish or electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-


Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.

Fitting accessories ordered separately.


LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam Power supply included. IP20 | 230Vac | 50/60Hz



4000K	Light Source	Luminaire
Power	53W	62,4W
Flux	7500lm	6000lm
Efficiency	142lm/W	96lm/W
LOR	-	80%
UGR	-	<19



mm	<i>L</i> 47x2923



Finishes

O .01 White / RAL 9010 ● .02 Black / RAL 9005

Mandatory 51027 Recessed fitting accessory

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

2933