



27+56W / 2720+2560lm / 3000K / DALI / Flood 64° / batwing / 2344mm

60534



Design: OM + Bartenbach GmbH Pendant direct and indirect luminaire with housing made of aluminium in matte finish.


Aluminium anodised end caps with matt finish. Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.

Indirect light: Lenses for batwing effect protected by a transparent polycarbonate diffuser. Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam Power supply included. IP20 | 230Vac | 50/60Hz



| 1000K | Light Source | Luminaire |
|------------|--------------|-------------|
| Power | 27+56W | 32+64W |
| Flux | 3360+3200lm | 2720+2560lm |
| Efficiency | 79lm/W | 53lm/W |
| LOR | - | 80% |
| UGR | - | <13 |



Beam angle Flood 64° / batwing

Application



Weight 8,2Kg

| | shes | |
|---------|------|--|
| II II G | | |


O .04 Matt White

.05 Matt Black

Mandatory 59054 Pendant direct/indirect fitting accessory 56051 Clear Base DALI ø60x35mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com





mm