

inFinit Recessed

45W* / 4800lm* / 2200K-5000K / DALI / Flood 64° / 2357mm

60550



Design: OM + Bartenbach GmbH

Recessed luminaire with housing made of aluminium with 25 micron maximum corrosion resistance anodization in matte finish or electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-


Linear extruded lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 2-step MacAdam Power supply included. IP20 | 230Vac | 50/60Hz



1 2200K-5000K	Light Source	Luminaire
Power	45W*	52,7W*
Flux	6000lm*	4800lm*
Efficiency	134lm/W	91lm/W
LOR	-	80%
UGR	-	<13



mm 47x2347

> Mandatory 51027 Recessed fitting accessory

O .01 White / RAL 9010 ● .02 Black / RAL 9005

Finishes

O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. 2357 For other type of material please contact: support@om-light.com

