

16W / 740lm / 2700K / On/Off / Wallwasher /
615mm

60562



Design: OM + Bartenbach GmbH
 Recessed luminaire with housing made of aluminium with 25 micron maximum corrosion resistance anodization in matte finish or electrostatic 100% polyester paint with textured finish.
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured finish.
 Linear extruded lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.
 Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
 Power supply included.
 IP20 | 230Vac | 50/60Hz



LED 2700K

Light Source Luminaire


Power 16W 19,5W

Flux 1600lm 740lm

Efficiency 100lm/W 38lm/W

LOR - 46%

UGR - -

Beam angle
Wallwasher

Application

Weight
1,64Kg

47x605

47x605

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

Mandatory

51027 Recessed fitting accessory

O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

