

16W / 740lm / 3000K / On/Off / Wallwasher
/ 611mm

60586



Design: OM + Bartenbach GmbH

Surface or pendant luminaire with housing made of aluminium with 25 micron maximum corrosion resistance anodization in matte finish or electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

Linear extruded lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.

Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz



LED	3000K	Light Source	Luminaire
Power	16W		19,5W
Flux	1600lm		740lm
Efficiency	100lm/W		38lm/W
LOR	-		46%
UGR	-		-




Beam angle
Wallwasher

Application



Weight
1,64Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

Mandatory


54036 Pendant direct fitting accessory

54034 Clear Base

ø60x35mm

Pendant direct fitting
accessory



54036



One 2m steel cable (1,2mm)
Max interval 3m

Clear Base

54034



On/Off (3x0,75mm²). Includes:
One clear polycarbonate power supply base (IP20).
One clear power cable (2m).
One clear power supply base must be applied every 30m (ø60x35mm)