

52W / 3920lm / 3000K / DALI / Flood 52° /
1211mm

60681



Design: O/M + Bartenbach GmbH
Surface or pendant luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision35 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source.

Fitting accessories for pendant version ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



3000K

Light Source **Luminaire**


Power **52W** **61,2W**

Flux **5160lm** **3920lm**

Efficiency **99lm/W** **64lm/W**

LOR **-** **76%**

UGR **-** **<16**



Beam angle
Flood 52°



Weight
2,4Kg

mm

Finishes

- .01 White / RAL 9010**
- .02 Black / RAL 9005**

Mandatory

54036 Pendant direct fitting accessory

56051 Clear Base DALI

ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

