

## inVision35 Surface/Pendant

27W / 2520lm / 4000K / DALI / Medium 31º / 1211mm

60694



Design: O/M + Bartenbach GmbH Surface or pendant luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.


Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision35 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source. Fitting accessories for pendant version ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam Power supply included. IP20 | 230Vac | 50/60Hz



1000K	Light Source	Luminaire
Power	27W	32,9W
Flux	3440lm	2520lm
Efficiency	127lm/W	77lm/W
LOR	-	73%
UGR	-	<10



Beam angle Medium 31° Application Weight 2,4Kg

Finishes

O .01 White / RAL 9010 ● .02 Black / RAL 9005

Mandatory 54036 Pendant direct fitting acessory 56051 Clear Base DALI ø60x35mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com



