



46W* / 2840lm* / 2200K-5000K / DALI / Flood 52° / 1211mm

60705



Design: O/M + Bartenbach GmbH Surface or pendant luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.


Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision35 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source. Fitting accessories for pendant version ordered separately.

LED >80CRI<90 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. DALI DT8. IP20 | 230Vac | 50/60Hz







● 2200K-5000K	Light Source	Luminaire
Power	46W*	58W*
ilux	3760lm*	2840lm*
fficiency	82lm/W	49lm/W
OR	-	76%
JGR	-	<16
ifficiency OR	82lm/W -	49lm/W 76%

mm



Finishes

O .01 White / RAL 9010 ● .02 Black / RAL 9005

Mandatory 54036 Pendant direct fitting acessory 56051 Clear Base DALI ø60x35mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com