

U35 Surface/Pendant

40W / 3550lm / 2700K / On/Off / Diffuse / 2831mm

60808



Design: Eduardo Souto de Moura Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint. Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.


Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP40 | 230Vac | 50/60Hz



● 2700K	Light Source	Luminaire
Power	40W	47,1W
Flux	7000lm	3550lm
Efficiency	175lm/W	75lm/W
LOR	-	51%
UGR	-	<25



Beam angle Diffuse Application Weight

mm



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005 .10 Anodised aluminium

Mandatory

54036 Pendant direct fitting acessory 54034 Clear Base

ø60x35mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C and D

Model Identifier 89603210, 89603215