

## **U35** Made-to-measure

41W / 3960lm / 4000K / On/Off / Diffuse / 1679mm

60919

Design: O/M


LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP20 | 230Vac | 50/60Hz



| 0                     |                       |
|-----------------------|-----------------------|
| Structure             | Diffuser              |
| 1 Profile             | A Polycarbonate frost |
| 2 End caps            | diffuser              |
| 3 Fitting accessories | Light Source          |
| 4 Profile coupling    | B LED Modules         |

| 1000K      | Light Source | Luminaire |
|------------|--------------|-----------|
| Power      | 41W          | 48,2W     |
| Flux       | 7800lm       | 3960lm    |
| Efficiency | 190lm/W      | 82lm/W    |
| LOR        | -            | 51%       |
| UGR        | -            | <28       |



Diffuse Application

Beam angle

Weight 0,6Kg

mm

## 31

## Finishes

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

Data according to regulations 2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier 89603217