

20W / 1630lm / 2700K / DALI / Diffuse /
1429mm

61109



Design: Eduardo Souto de Moura
 Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
 Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.
 Fitting accessories ordered separately.


LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
 Power supply included.
 IP40 | 230Vac | 50/60Hz



2700K

Light Source Luminaire

| | | |
|------------|---------|--------|
| Power | 20W | 24,4W |
| Flux | 3500lm | 1630lm |
| Efficiency | 175lm/W | 67lm/W |
| LOR | - | 47% |
| UGR | - | <25 |



Beam angle
Diffuse





Weight
2,3Kg

1429 mm

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium



Mandatory

54036 Pendant direct fitting accessory
 56051 Clear Base DALI
 ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:
 support@om-light.com

Data according to regulations
 2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class C
 and D
 Model Identifier 89603210, 89603215