U45
Made-to-measure

7,9W / 650lm / 2700K / On/Off / Diffuse / 559mm

61302

Design: O/M

LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



Structure
1 Profile
2 End caps
3 Fitting accessories
4 Profile coupling

Diffuser
A Polycarbonate frost diffuser

Light Source
B LED Modules

LED 2700K	Light Source	Luminaire
Power	**7,9W**	**9,9W**
Flux	**1400lm**	**650lm**
Efficiency	**177lm/W**	**66lm/W**
LOR	**-**	**46%**
UGR	**-**	**<25**



Beam angle
Diffuse

Application



Weight
0,5Kg

mm



Finishes

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class D
Model Identifier 89603215

www.om-light.com / mail@om-light.com Rua Maurício Lourenço Oliveira 186, 4405-034 Vila Nova de Gaia, Porto. Portugal. / Apartado 1538 4401-901 Vila Nova de Gaia, Porto Portugal / tel. +351 223 710 419