

41W / 3360lm / 2700K / DALI + E-KIT /  
Diffuse / 1679mm

61333

Design: O/M

LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



### Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling


### Diffuser

- A Polycarbonate frost diffuser

### Light Source

- B LED Modules

LED	2700K	Light Source	Luminaire
Power		41W	48,2W
Flux		7170lm	3360lm
Efficiency		175lm/W	70lm/W
LOR		-	47%
UGR		-	<25




Beam angle  
Diffuse

### Application



Weight  
0,8Kg



### Finishes

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class D  
Model Identifier 89603215