

17W / 1437,5lm / 3000K / On/Off / Diffuse /  
699mm

61339

Design: O/M

LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



#### Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

#### Diffuser

- A Polycarbonate frost diffuser

#### Light Source

- B LED Modules

| LED        | 3000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power      |       | 17W          | 20,7W     |
| Flux       |       | 3062,5lm     | 1437,5lm  |
| Efficiency |       | 180lm/W      | 69lm/W    |
| LOR        |       | -            | 47%       |
| UGR        |       | -            | <25       |




Beam angle  
Diffuse

Application



Weight  
0,5Kg

mm



#### Finishes

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: [support@om-light.com](mailto:support@om-light.com)

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603206, 89603216