

54W / 4600lm / 2700K / DALI / Diffuse /  
2271mm

61573



Design: Eduardo Souto de Moura  
 Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.  
 Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.  
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.  
 Fitting accessories ordered separately.


LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
 Power supply included.  
 IP40 | 230Vac | 50/60Hz



2700K

Light Source Luminaire

Power	54W	63,5W
Flux	9560lm	4600lm
Efficiency	177lm/W	72lm/W
LOR	-	48%
UGR	-	<25



Beam angle  
Diffuse



Weight  
5Kg

mm

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium



Mandatory

54036 Pendant direct fitting accessory  
 56051 Clear Base DALI  
 ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:  
 support@om-light.com

Data according to regulations  
 2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
 supplemented by 2021/340/EU Energy Consumption Labelling  
 Ordinance. This product contains light sources of efficiency class D  
 Model Identifier 89603215