

20W / 1815lm / 4000K / On/Off / Diffuse /
1429mm

61594



Design: Eduardo Souto de Moura
 Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
 Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
 Power supply included.
 IP40 | 230Vac | 50/60Hz



4000K

Light Source **Luminaire**


Power **20W** **24,4W**

Flux **3775lm** **1815lm**

Efficiency **189lm/W** **74lm/W**

LOR **-** **48%**

UGR **-** **<25**



Beam angle
Diffuse



Weight
3,1Kg

mm

Finishes

- .01 White / RAL 9010**
- .02 Black / RAL 9005**
- .10 Anodised aluminium**

Mandatory

54036 Pendant direct fitting accessory

54034 Clear Base

ø60x35mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class C
 Model Identifier 89603212, 89603217

