

27W / 2500lm / 4000K / DALI / Diffuse /
1149mm

61601



Design: Eduardo Souto de Moura
 Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
 Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
 Power supply included.
 IP40 | 230Vac | 50/60Hz



4000K

Light Source **Luminaire**


Power **27W** **32,9W**

Flux **5200lm** **2500lm**

Efficiency **193lm/W** **76lm/W**

LOR **-** **48%**

UGR **-** **<25**



Beam angle
Diffuse



Weight
2,5Kg

mm

Finishes

- .01 White / RAL 9010**
- .02 Black / RAL 9005**
- .10 Anodised aluminium**


Mandatory

54036 Pendant direct fitting accessory

56051 Clear Base DALI

ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:
 support@om-light.com



Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class C
 Model Identifier 89603217