

20W / 1675lm / 2700K / DALI / Diffuse /  
1429mm

61714



Design: Eduardo Souto de Moura  
 Surface luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.  
 Frosted polycarbonate diffuser with user friendly clipping system.  
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.  
 Fitting accessories not included.


LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
 Power supply included.  
 IP54 | 230Vac | 50/60Hz



2700K

**Light Source** Luminaire

<b>Power</b>	<b>20W</b>	<b>24,4W</b>
<b>Flux</b>	<b>3500lm</b>	<b>1675lm</b>
<b>Efficiency</b>	<b>175lm/W</b>	<b>69lm/W</b>
<b>LOR</b>	-	<b>48%</b>
<b>UGR</b>	-	<b>&lt;25</b>



**Beam angle**  
**Diffuse**



**Weight**  
**3,1Kg**

mm

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

For the specific supply of "DALI 2" drivers, please contact:  
[support@om-light.com](mailto:support@om-light.com)



Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
 supplemented by 2021/340/EU Energy Consumption Labelling  
 Ordinance. This product contains light sources of efficiency class C  
 and D  
 Model Identifier 89603210, 89603215