

## U60 IP54 Surface

34W / 2925lm / 3000K / On/Off / Diffuse /  
1429mm

61723




Design: Eduardo Souto de Moura  
Surface luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.  
Frosted polycarbonate diffuser with user friendly clipping system.  
Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.  
Fitting accessories not included.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP54 | 230Vac | 50/60Hz



LED	3000K	Light Source	Luminaire
Power		34W	40W
Flux		6125lm	2925lm
Efficiency		180lm/W	73lm/W
LOR		-	48%
UGR		-	<25




Beam angle  
Diffuse

Application



Weight  
3,1Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603211, 89603216