

U60 IP54 Surface

34W / 3125lm / 4000K / On/Off / Diffuse /
1429mm

61739




Design: Eduardo Souto de Moura
Surface luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
Frosted polycarbonate diffuser with user friendly clipping system.
Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.
Fitting accessories not included.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP54 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		34W	40W
Flux		6500lm	3125lm
Efficiency		191lm/W	78lm/W
LOR		-	48%
UGR		-	<25




Beam angle
Diffuse

Application



Weight
3,1Kg

mm



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C
Model Identifier 89603212, 89603217