

28W / 2960lm / 2700K / On/Off / Prismatic /
2271mm

61852



Design: Eduardo Souto de Moura
 Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
 Prismatic polycarbonate diffuser with low luminance and glare control (UGR<19 for low output or UGR<22 for High Output).
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
 Power supply included.
 IP40 | 230Vac | 50/60Hz



2700K

Light Source **Luminaire**


Power **28W** **32,9W**

Flux **4800lm** **2960lm**

Efficiency **171lm/W** **90lm/W**

LOR **-** **62%**

UGR **-** **<19**



Beam angle
Prismatic

Application



Weight
5Kg

mm

Finishes

- .01 White / RAL 9010**
- .02 Black / RAL 9005**
- .10 Anodised aluminium**

Mandatory

54036 Pendant direct fitting accessory

54034 Clear Base

ø60x35mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class D
 Model Identifier 89603215



- 60 -